

# VUTX.EX28282 - PRESSURE-REDUCING AND -RESTRICTING DEVICES

## Pressure-reducing and -Restricting Devices

See General Information for Pressure-reducing and -Restricting Devices

### SENSOR TECH FIRE FIGHTING AND SAFETY EQUIPMENT TRADING

EX28282

P.O. BOX 231728, OFFICE NO.506,AL SAOUD BUILDING,AL QUSAIS-4

DUBAI, UNITED ARAB EMIRATES

#### Reducing valves

Model	Valve Type	Body Type	NPS	Bonnet Type*	End Configuration Inlet by Outlet	Max Rated Inlet Pressure, psig	Supervisory Switch+
F11	Restricting - Adjustable	Angle	1.5	—	Female X Male Female X Female	175	—
F22	Restricting - Adjustable	Angle	2.5	—	Female X Male Female X Female	175	—

\* Different bonnet configurations are selected based upon inlet pressure conditions and desired outlet pressure.

+ I = Indoor installation; O = Outdoor installation

NPT - National Pipe Thread

Last Updated on 2020-01-14

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"