



# HLCV.EX27839 - STRAINERS, PIPELINE

## Strainers, Pipeline

See General Information for Strainers, Pipeline

### SENSOR TECH FIRE FIGHTING AND SAFETY EQUIPMENT TRADING

EX27839

P.O. BOX 231728, OFFICE NO.506,AL SAOUD BUILDING,AL QUSAIS-4

DUBAI, UNITED ARAB EMIRATES

**Strainers, Y- type, 2, 2.5, 3, 4, 5, 6, 8, 10 and 12 in. sizes, for rated working pressure of 300 psi or 2070 kPa, Model(s) ST1701-300, ST1702-300, ST1703-300**

NOTE - Loss of head will approximate 7.22 psi (49.78 kpa) for the 2 in. size at 157.63 GPM, 5.89 psi (40.61 kpa) for the 2-1/2 in. size at 224.86 GPM, 8.24 psi (56.81 kpa) for the 3 in. size at 347.53 GPM, 5.88 psi (40.54 kpa) for the 4 in. size at 598.54 GPM, 7.63 psi (52.61 kpa) for the 5 in. size at 940.7 GPM, 4.82 psi (33.23 kpa) for the 6 in. size at 1358.85 GPM, 5.83 psi (40.20 kpa) for the 8 in. size at 2405.84 GPM, 7.25 psi (49.99 kpa) for the 10 in. size at 3795.17 GPM and 5.73 psi (39.51 kpa) for the 12 in. size at 5442.11 GPM.

Trademark and/or Tradename: **FWIC Valve**

Last Updated on 2018-09-23

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"